



**VIVID PIXEL INSTALLATION  
CL-DMX-2900 DECODER IN TESTING MODE**

NOTES:

1. DIAGRAM REFER TO SINGLE FEED MAX. RUN LENGTH. LONGER FIXTURES MAY REQUIRE 24V POWER SUPPLY CONNECTED TO BOTH ENDS.
2. CHECK NEON FLEX SPECIFICATION SHEETS FOR MAXIMUM RUN LENGTHS OF YOUR PIXEL FIXTURE MODEL AND COLOR.
3. DIAGRAM FOR WIRE CONNECTION REFERENCE ONLY. FOR TOTAL POWER AND NUMBER OF CHANNELS REQUIRED ON YOUR APPLICATION, CHECK SPECIFICATION SHEETS OF EACH PRODUCT.

BOM:

1. 24V POWER SUPPLY
2. NEON FLEX PIXEL (S160, S270, WAVE, WAVE 320)
3. CL-DMX-2900

Product:

NEON FLEX PIXEL (S160, S270, WAVE, WAVE 320)

Project:

SUPPORT WIRING DIAGRAMS

Title:

PIXEL - CL-DMX-2900 DECODER

Date: SEPT. 10, 2018

Drawn: HILLARY

Scale: NTS Rev: 01