

Stud Mount Acrylic Signage

Installation Instructions For Flat or Uneven Mounting Surfaces

Tools required:

Mounting Pattern
Level
Drill & Drill Bit
Tape Measure

Dusting Cloth or Cleaning Supplies
Masking Tape
3M Commercial Grade Adhesive

1. Make sure all studs are inserted into the acrylic lettering or signage.




2. Remove any dust or dirt from the mounting surface.

Using a level, align the mounting pattern on the surface and secure with masking tape.
(Note: brick or cement walls may require a stronger tape, such as duct tape, to keep the pattern in place.)



Mark the drill holes on the surface using a center punch or sharpie. Remove the pattern before drilling to make sure it is accurate.



3. Drill the marked holes using a drill bit that is appropriate for your mounting surface and slightly larger in diameter than the studs. This will allow for adjustments if necessary.

Making sure to hold the drill level, drill all marked holes at least 1.5in (38mm) deep.

Remove all dust from the drilled holes before moving on to the mounting.



For More Information

Toll Free: 1 (888) 580-6366

Or Visit www.GLLS.com/contact-us/

www.GLLS.com

4. Before applying any adhesive, test the position of the mounting holes by gently inserting the studs.

If they don't easily press into the holes, carefully enlarge the holes to fit the studs.



5. Fill the drill holes with a generous amount of 3M Commercial Grade Adhesive. Coat the studs with the same adhesive.

Press the studs into place until the back of the piece of signage is flush with the mounting surface. Secure the piece to the wall using tape appropriate for the surface.

Repeat this process until all pieces of the sign are in place.



6. Check the placement of the sign pieces from a distance.

Adjust them as necessary, removing and repositioning the tape as needed. Make sure the letters are securely held in place, using more tape if necessary.



7. Once the adhesive is dry (time may vary depending on the climate), remove the tape and the protective plastic.

Clean the face of the sign if needed.

For More Information

Toll Free: 1 (888) 580-6366

Or Visit www.GLLS.com/contact-us/